

UNO 105

Fluid Spray

DESCRIPTION

UNO 105 Spray Fluid is a wire rope & chain lubricant that is used for primary lubrication and conservation of the rope & chain.

TYPICAL APPLICATION

- It is used for prevention of corrosion and wear for chain & ropes in the fields Off-shore, fishing ropes and sea transportation.

BENEFITS

- It has light clear color and forms a solid and elastic layer on metal surfaces. Depending on layer thickness, a closed layer arises that protects the surfaces perfectly against the influence of seawater

FRANCOL INTERNATIONAL PTE LTD

Website: www.francol.com.sg
Tel: 65 67492426 Fax: 65 67492428

UNO 105
Fluid Spray

TYPICAL PROPERTIES

Temperature	
Dropping point	Above 80 °C
Breaking point (75g/m ²)	Below -40 °C
Application temperature	120 °C - 150 °C
Flash point	Above 200 °C
Viscosity (100 °C)	Ca. 1500mm ² /s
Hardness & Consistency	
Characteristic Penetration	Ca. 120 1/10 mm

This information in this bulletin is, to our best knowledge, true and accurate, but all recommendation or suggestions are made without guarantee, since the conditions of use are beyond our control. It is the user's obligation to evaluate and use the product safely and to comply with all applicable laws and regulations.

Specifications as at January 2005